

HURRICANE II HEADSET



Recommended for public safety markets, manufacturing, airline industries and all users in high noise environments.

The **Hurricane II headset** is designed to provide the performance of a heavy duty headset in a high noise environment without all of the weight and bulk. The dual ear loops ship standard with NoisEzSM Ear Tips with an NRR rating of 29dB, delivering advanced protection against dangerous decibel levels. The user can easily convert the headset for use in a low noise environment by simply switching out the ear tips. The closefitting headset can be worn comfortably under a helmet or cap.

Mechanical Specifications:

- Cable pull from T module, axial: 30 lbs
- Cable pull from headset, axial: 20 lbs
- Wire pull from receiver, axial: 20 lbs
- Receiver wire pull from headset, axial: 20 lbs
- Flex at connector: 25,000 cycles
- Cable flex at T module: 6,000 cycles
- Cable flex at headset: 15,000 cycles
- Cable flex at receiver: 5,000 cycles
- Wireform flex (tip to tip): 25,000 cycles
- 24 month manufacturer's warranty

Electrical Specifications:

- Microphone sensitivity at 94dB SPL: -44 typical

Environmental Specifications:

- Operating temperature: -20° C to +60° C
- Storage temperature: -40° C to +80° C

Be clear, stay connected.

Visit www.ottoexcellence.com or call toll-free 888-234-OTTO (6886) or direct 1-847-428-7171.