

G1

The Only Submersible Voice Pager

DESIGNED FOR PUBLIC SAFETY



IP67 Rating

Waterproof
Dustproof

Available in

Low Band, VHF, UHF

Scan Modes

Free, Silent,
Normal, Priority

2 Year Warranty

With additional 3 years

Standard Features

Bluetooth

Voice Memo

Voice Storage

AAA Batteries

Up to 64 Channels

Programmable Music
& Voice Alerts



The G1 is rich with standard features including 16 minutes of stored voice and 11 minutes of voice memo. This enables you to record your own personal messages for on-the-scene reminders, notes, etc! The included Bluetooth allows you to pair your G1 with other devices. There are seven different backlight color options that allow you to assign colors to different channels.

This device is a software-defined pager that allows for updates with the latest features. Don't miss out on the most rugged voice pager on the market! With included features and units in stock, we have your back while you serve your community! Available in Red, Yellow, Black, and Pink.

Get Connected:
Follow us  :

www.UnicationUSA.com
www.Facebook.com/UnicationUSA




G1 STANDARD FEATURES

Signaling Options:
 2 Tone, 5/6 Tone
 CDCSS(DPL), CTCSS(PL)
AAA Batteries: Rechargeable or Alkaline
 16 Minutes voice storage
 11 Minutes voice memo
 7 Backlight colors
 64 Channels
 Rejects cellphone interferences
 Message Lock
 Duty On/Off feature
 Auto On/Off feature
 Bluetooth (compatible with most phones and headsets)
Scan Modes:
 Normal (Probability Scan)
 Free, Priority, Silent, Monitor, Selective
 Standard 2 years warranty (5 years optional)

ADDITIONAL INFORMATION

Best in class message reception
 Submersible to 3 ft. for up to 30 minutes.
 Software-defined technology
 Weighs 200g
 Dimensions (mm)
 100.5 x 65.2 x 26.45
 Charger comes standard
 Charger detects alkaline and rechargeable batteries
 Charger Amplifier (optional):
 Extensive input, output control
 Heavy duty belt clip
 Temperature range: -10 C ~ +50 C
 Special rubberized housing

TECHNICAL SPECIFICATIONS

RF Perf/Band	Low	VHF	UHF	
Sensitivity/Alerting (uV/m)	3.5	2	3	
Sensitivity/12dB SINAD (uV/M)	9	8	9	
Frequency Stability (ppm)	+ -10	+ -3	+ -3	
Adjacent Channel Selectivity	70/65dB		25/12.5kHz (VHF)	
Spurious	>70dB			
Image Rejection	>70dB			
Audio Output Linear	>300mw			
Audio Distortion	<3%			
SPL Output (12")	96dB			
Speech Output (12:)	94dB			
Dust/Water Proof Level	IP67			
UL	Class I, Div. II			
FCC	FCC Part 15			
MIL-STD	810E, Procedures 1 for Driving Rain			
Channel Spacing	Narrowband or Wideband			
Frequency Band	Low Band	VHF	UHF	
Frequency Range (MHz)	33-39	137-153	450-470	
	43-49	148-164	465-485	
			495-512	



Reliable. Rugged. Built to Last.